



# color<sup>tools</sup><sup>TM</sup>

## Oil Base Glaze - Neutral

Product Code: **300637**

Colortools™ Oil Base Glaze is a neutral tintable wiping glaze for achieving specialty finishes on high quality kitchen cabinets, interior doors & millwork and other wood products.

### CHARACTERISTICS:

Coverage:	300 - 500 sq. ft. per gallon depending on application method and absorbency of substrate.
Dry Time:	Times may vary due to environmental controls, humidity and application method.
Dry to handle:	10 minutes @ 65-70° F.
Dry to Seal:	See Directions for Use (below)
Storage:	Keep container closed when not in use. Store in the original container. Do not store above 100°F (37.8°C).
Shelf Life:	12 months from date of manufacture.
VOC:	661- 697 g/l (5.51 - 5.82 lb/gal)*
HAP:	Pounds HAP per Pound Solids 0.10-0.16*
* VOC and HAP content will vary with color and tint strength.	

### TINTING:

Maximum color load is 8 fluid ounces per gallon of glaze. Tint with Colortools Solvent Base Colorants or 844 Colorants.

### SURFACE PREPARATION:

Sand wood surface with 150 grit aluminum oxide sandpaper until you achieve a white powder. Remove sanding dust from surface. Surface should be free of dirt, grease, oils, wax and sanding dust.

### DIRECTIONS FOR USE:

Stain the piece, if desired, and allow recommended dry time for stain type.

Apply seal coat and allow to dry thoroughly. Note: Seal coat must seal off the open grain of the wood or the glaze will penetrate the substrate and be unable to remove. When using a lower solids clear lacquer as the finish, the first finish coat may be used to seal the open grain prior to glazing.

Sand the seal coat (or first finish coat) with 180 or finer silicon carbide sandpaper.

Apply Glaze at full strength to select areas or entire door, depending upon desired effect. Allow to set up briefly, approximately 2-5 minutes. Use a clean damp cloth to carefully remove the glaze from high and open areas.

**This product must be top-coated.**

**Dry Times:** Thin applications on flat surfaces and simple relief—allow approximately 3 hours before coating. **Thick applications** such as crevasses, beading, routing or other deep recesses, **require an overnight dry before finishing.**

**Application Equipment:** Product can be applied with most spray application equipment: conventional air-spray, airless, air-assisted airless, or H.V.L.P. spray equipment. A brush or rag can used for small areas.

**Thinning:** Thinning is not required, however, if desired, thin with a small amount of Mineral Spirits. Thinning may result in color variation.

**Clean-Up:** Clean equipment immediately with Mineral Spirits or Lacquer

### FEATURES:

- Great 'open time'
- Excellent workability
- Easy to wipe
- Achieve a variety of decorative effects with different application techniques
- Produce subtle highlights or dramatic color combinations
- Use with stained or solid color backgrounds
- Tint base provides limitless color options

### APPLICATION PRECAUTIONS

Colortools Oil Base Glaze must be thoroughly dry to avoid loss of adhesion over, under and between clear sealers or topcoats.

Always remove excess glaze to maximize adhesion of finishes.

Glazes are decorative finishes and may not be suitable for use in some high wear areas. This product has been tested with a limited number of substrates, seal coats and topcoats. The user is responsible for testing suitability and performance for their specific application.

*Avoid breathing vapors, use a NIOSH approved cartridge respirator. Use filters to avoid breathing spray particles or sanding dust. Read label and Safety Data Sheet before using.*

DANGER - RAGS, STEEL WOOL OR WASTE SOAKED WITH STAIN OR GLAZE MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER USE, PLACE RAGS, STEEL WOOL OR WASTE IN SEALED WATER-FILLED METAL CONTAINER. DISPOSE OF ACCORDING TO FEDERAL, STATE OR LOCAL REGULATIONS.

### SHIPPING/STORAGE INFORMATION:

Flash Point\*: < 73° F. Pensky-Marten  
 OSHA Flammability Class: Flammable Liquid - Class IB  
 DOT Class: UN 1263, Paint, 3, PG II

\* Variations depend on color.



421 SE 27th St, El Reno, OK 73036  
 Tel: (800) 444-7833  
 ruddwoodfinishes.com

© Gemini Industries, Inc. 11.2025

