

SECTION 1: IDENTIFICATION

Product Name	MiraVar 275 Opaque CV Sanding Sealer White
Product Code #	310668.00
Manufacturer	Gemini Industries, Inc.
Address	421 SE 27th Street El Reno, OK 73036
Phone	Local: (800) 262-5710 Toll Free: (800) 444-7833
Emergency Contact	CHEMTREC (24HR Emergency Telephone), call: 1-800-424-9300 International CHEMTREC, call: 1-800-255-3924
Recommended Use/Restrictions	For Wood Substrates Only.

SECTION 2: HAZARD(S) IDENTIFICATION

Classifications	Acute Toxicity - Oral: Category 4 Acute Toxicity - Skin: Category 4 Acute Toxicity - Inhalation: Category 4 Skin Corrosion: Category 3 Eye Damage/Irritant: Category 1 Skin sensitization: Category 1B Carcinogenicity: Category 2 STOT Single Exposure: Category 3 STOT Repeated Exposure: Category 1 Flammable Liquid: Category 2
------------------------	--

Pictograms

Signal Word

Danger

Hazard Statements

H302 | Harmful if swallowed.
 H312 | Harmful if in contact with skin.
 H332 | Harmful if inhaled.
 H316 | Causes mild skin irritation.
 H318 | Causes serious eye damage.
 H317 | May cause an allergic skin reaction.
 H351 | Suspected of causing cancer.
 H336 | May cause drowsiness or dizziness.
 H372 | Causes damage to organs through prolonged or repeated exposure.
 H225 | Highly flammable liquid and vapor.

Precautionary Statements

P210 | Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 P233 | Keep container tightly closed.
 P240 | Ground/bond container and receiving equipment.
 P241 | Use explosion-proof electrical/ventilating/lighting/other equipment.
 P242 | Use only non-sparking tools.
 P243 | Take precautionary measures against static discharge.
 P201 | Obtain special instructions before use.



MiraVar 275 Opaque CV Sanding Sealer White

P202 | Do not handle until all safety precautions have been read and understood.
P260 | Do not breathe dust/fume/gas/mist/vapors/spray.
P261 | Avoid breathing dust/fume/gas/mist/vapors/spray.
P264 | Wash any exposed body parts thoroughly after handling.
P270 | Do not eat, drink or smoke when using this product.
P271 | Use only outdoors or in a well-ventilated area.
P272 | Contaminated work clothing should not be allowed out of the workplace.
P280 | Wear protective gloves/protective clothing/eye protection/face protection.
P281 | Use personal protective equipment as required.
P301 + P312 | IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
P302 + P352 | IF ON SKIN: Wash with plenty of soap and water.
P303 + P361 + P353 | IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340 | IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305 + P351 + P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 | IF exposed or concerned: Get medical advice/attention.
P310 | Immediately call a POISON CENTER or doctor/physician.
P314 | Get medical advice/attention if you feel unwell.
P321 | Specific treatment (see supplemental first aid instruction on this label if immediate administration of antidote/specific measures/cleansing agent/immediate measures is/are appropriate/required).
P322 | Specific measures (see supplemental first aid instruction on this label if immediate measures such as specific cleansing agent is advised).
P330 | Rinse mouth.
P333 + P313 | If skin irritation or rash occurs: Get medical advice/attention.
P363 | Wash contaminated clothing before reuse.
P370 + P378 | In case of fire: Use appropriate media for extinction if water increases risk.
P403 + P233 | Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 | Store in a well-ventilated place. Keep cool.
P405 | Store locked up.
P501 | Dispose of contents/container to appropriate waste disposal entity in accordance with local/regional/national/international regulation.

Percent of the mixture consisting of ingredient(s) of unknown toxicity

To the best of our knowledge, there are no additional ingredient(s) present requiring hazardous reporting or health warnings.

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

Reportable Components	% of Comp.	CAS No.
1-CHLORO-4-(TRIFLUOROMETHYL)-BENZENE	20 - 30%	98-56-6
ACETONE	10 - 20%	67-64-1
TALC (NON-FIBROUS)	5 - 10%	14807-96-6
TITANIUM DIOXIDE	5 - 10%	13463-67-7
N-BUTYL ALCOHOL	1 - 5%	71-36-3
METHYL AMYL KETONE	1 - 5%	110-43-0
ETHYL BENZENE	< 1.0%	100-41-4

**SECTION 4: FIRST AID MEASURES**

General Advice	Have Safety Data Sheet available when calling Poison Control Center (1-800-222-1222) or physician; or when going to the emergency room.
Eyes	Immediately flush eye with plenty of water for 15 minutes, while lifting upper and lower eyelids. Remove contact lenses if present and easy to do. Continue rinsing. Check eye for chemical burns. Get medical attention. May cause eye burns. Get medical attention.
Skin	Immediately wash with soap and water. Remove contaminated clothing and shoes. Wash or clean thoroughly before reuse. Get medical attention if irritation persists.
Inhalation	Remove to exposure to fresh air. If breathing is difficult, give oxygen. If breathing is stopped, give artificial respiration. Keep person warm and quiet. Get medical attention.
Ingestion	DO NOT INDUCE VOMITING! Call Poison Control Center, (1-800-222-1222) or physician immediately. NOTE: Aspiration of solvents may result in chemical pneumonia.

SECTION 5: FIRE FIGHTING MEASURES

Fire Hazard	Yes
Extinguishing Media	Foam, CO2, Dry Chemical, Water Mist
Special Protective Equipment and Firefighting Procedures	Evacuate all unnecessary personnel. Use full protective equipment. Cool closed containers to prevent pressure build-up and possible explosion. Direct water stream is not recommended for oil base fires. Product may float and reignite on surface of water. Do not allow product or runoff from fire control measures to enter storm or sanitary sewers or waterways.
Unusual Fire & Explosion	Explosive vapor mixtures may form which is dangerous when exposed to heat and flame. Vapors are heavier than air and may travel along the ground, or be moved by ventilation, and ignited by pilot lights, stoves, heaters, electric motors, sparks, flame, smoking, static discharge or other ignition sources even at location distant from material handling site. Free falling stream of liquid may cause static electricity build-up and create fire hazard.
Hazardous Combustion Products	See Section 10

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions	Avoid any uncontrolled release of material. Wear chemical splash goggles, impervious gloves, appropriate respirators, and protective clothing until all hazards are known.
Spills / Leaks	If spill/leak occurs, eliminate ignition sources and ventilate area. Evacuate all unnecessary personnel. Wear full protective equipment. Dike drains to prevent entering storm or sanitary sewers, rivers, streams, or waterways. Contain spill and cover with inert absorbent material. Clean using non-sparking tools (aluminum, brass, copper) and place mixture into containers for disposal. Note: Some spills/releases may require special reporting to local, state or federal agencies.



SECTION 7: HANDLING AND STORAGE

Handling

Handle using good industrial hygiene and safety practices. Avoid breathing vapors, spray mists, or dusts. Avoid contact with eyes and skin. Do not take internally. Use adequate ventilation, respiratory and personal protection. Avoid spraying hot surfaces.

Storage

Keep liquid and vapor away from heat, sparks, and flame. Turn off or remove all sources of ignition. Use proper methods of ventilation to prevent vapor buildup. Avoid contact with hot metal surfaces. Avoid free fall of liquids. Ground and bond fixed equipment, pails, drums and other transfer containers. Do not reuse, weld, drill, or heat empty containers which may contain explosive vapors.

Keep container closed when not in use and during transit. Store container in an upright position in a cool, dry environment and protect from damage. Use adequate ventilation. Follow label warnings until thoroughly cleaned or until container is sent for disposal. Do not remove or deface labels until empty containers have been destroyed or thoroughly cleaned. Do not transfer product to unlabeled containers. Do not store above 120 deg. F (50 deg. C).

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits

Chemical Description	OSHA PEL	ACGIH TLV	Other
1-Chloro-4-(trifluoromethyl)-benzene	NOT EST.	NOT EST.	NOT EST.
Acetone	1000 ppm	250 ppm	500 ppm STEL
Talc (non-fibrous)	20 mg/m3	2 mg/m3	NOT EST.
Titanium dioxide	15 mg/m3	10 mg/m3	NOT EST.
n-Butyl alcohol	100 ppm	20 ppm	(skin)
Methyl amyl ketone	100 ppm	50 ppm	233 mg/m3
Ethyl benzene	100 ppm	20 ppm	434 mg/m3

THIS PRODUCT CONTAINS A RESIN WITH THE POTENTIAL TO EMIT FORMALDEHYDE DURING USE. EXPOSURE LEVELS WILL VARY WITH SHOP CONDITIONS AND CONTROLS. BEFORE INITIAL USE, CONSULT OSHA'S FORMALDEHYDE STANDARD (29 CFR 1910.1048).

Engineering Controls

USE ONLY WITH ADEQUATE VENTILATION. Provide mechanical ventilation, local exhaust or other appropriate means of ventilation to prevent build-up of vapor or dust. Keep worker exposure to airborne contaminants below suggested or allowable limits. Keep area vapor and/or dust concentrations below lower explosive limits. Eye wash and safety showers are recommended in the workplace.

Personal Protective Equipment

Hand

Wear impermeable, chemical resistant gloves to prevent skin contact. Consult safety equipment supplier for specific recommendations of construction material. Wash hands with soap and water after using and before eating or using tobacco products.

Eyes

Wear chemical goggles designed to protect eyes against vapor, liquid splash and mists unless full-face respirator is worn. Ensure eye wash and safety showers are near workstations. NOTE: Contact lenses may contribute to the severity of an eye injury and should be removed immediately if exposure occurs.

Skin

Wear protective clothing, including headcap, to avoid skin contact with liquid or overspray. Thoroughly clean contaminated clothing and shoes before reuse.



MiraVar 275 Opaque CV Sanding Sealer White

Respiratory

USE ADEQUATE VENTILATION! Ensure fresh air entry during application and drying. If you experience eye watering, headache, dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved for the hazardous ingredients listed in Section 3) during and after application. If appropriate, use respirator pre-filter or dust/particle mask to avoid breathing sanding dust. Follow respirator manufacturer's instructions for use. Periodically monitor exposure levels to hazardous ingredients listed in Section 3 and review permissible exposure limits above.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Opaque liquid	Upper Flammability/Explosive Limit	12.80
Odor	Pungent solvent	Lower Flammability/Explosive Limit	0.90
pH value	No Data	Vapor Pressure	2.00
Freezing Point (F)	No Data	Vapor Density	2.00
Boiling Point (F)	No Data	Vapor Temperature	68.00
Boiling Range	133.00 - 304.00	Relative Density/Specific Gravity	10.07051
Flash Point (F)	-4.00	Solubility	Moderately Water Soluble
Flash Point Method Used	P Marten	Partition Coefficient	No Data
Evaporation Rate	Faster than butyl acetate	Auto-Ignition Temperature	No Data
Flammability	Yes	Decomposition Temperature	No Data
Viscosity	See Tech Data Sheet		

SECTION 10: STABILITY AND REACTIVITY

Chemical Reactivity	Will not occur.
Chemical Stability	Stable.
Conditions to Avoid	High temperatures, humidity, ignition sources and vapor build-up.
Materials to Avoid	Strong oxidizers, strong acids, strong bases
Hazardous Decomposition	Carbon Monoxide, Carbon Dioxide, Hydrocarbons, Aldehydes, Other Organic Compounds

SECTION 11: TOXICOLOGICAL INFORMATION**Acute Toxicity**

Reportable Components	LD50 Oral	LC50 Inhalation	LD50 Dermal
1-Chloro-4-(trifluoromethyl)-benzene	Not available	Not available	Not available
Acetone	5,800 mg/kg	50,100 mg/m3 (8H)	7,426 mg/kg
Talc (non-fibrous)	Not available	Not available	Not available



MiraVar 275 Opaque CV Sanding Sealer White

Titanium dioxide
n-Butyl alcohol
Methyl amyl ketone
Ethyl benzene

Not available
790 mg/kg
1,600 mg/kg
3,500 mg/kg

Not available
8,000 ppm (4H)
> 16 mg/l (4H)
Not available

Not available
3,400 mg/kg
> 5,000 mg/kg
15,433 mg/kg

Inhalation**Description of Effects From Short- and Long-Term Exposure:**

Vapors and mists irritate nose, throat, and lungs (burning, stinging, coughing). May cause headache, dizziness, nausea, weakness, shortness of breath and loss of coordination. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Exposure to extremely high vapor concentrations may cause unconsciousness and asphyxiation. Dust, sanding dusts and particles may cause nose and throat irritation. Harmful if inhaled.

Ingestion**Description of Effects From Short- and Long-Term Exposure:**

Causes nausea, vomiting, diarrhea and severe central nervous system depression (headache, dizziness, nausea, loss of coordination). Harmful if swallowed.

Eyes**Description of Effects From Short- and Long-Term Exposure:**

Contact with liquid or vapors causes severe irritation (redness, watering, itching, stinging, blurred vision) and possible cornea damage.

Skin**Description of Effects From Short- and Long-Term Exposure:**

Contact causes mild to severe irritation (dryness, itching, cracking, rash and swelling) and possible burns with prolonged contact. Harmful if in contact with skin. May cause an allergic skin reaction.

Carcinogen Information

Contains a chemical with the potential to cause cancer. Risk of cancer depends on level and duration of exposure.

Reportable Components: Ethyl benzene is classified as IARC 2B - possibly carcinogenic to humans. Titanium dioxide is classified by IARC as Group 2B a possible carcinogen based on animal studies (high concentration of dust may lead to lung cancer).

Carcinogens Listing

NTP	No
IARC	Yes
OSHA	No

SECTION 12: ECOLOGICAL INFORMATION**Aquatic Toxicity**

Acetone
Toxicity to Fish LC50: 5,540 mg/l - 96 h



Toxicity to Algae EC50: Not Available
n-Butyl alcohol
Toxicity to Fish LC50: 1,840 mg/l - 96 h
Toxicity to Algae EC50: Not Available

Methyl amyl ketone
Toxicity to Fish LC50: 126-137 mg/l - 96
Toxicity to Algae EC50: 98.2 mg/l - 72 h

Ethyl benzene
Toxicity to Fish LC50: 5.1 mg/l - 96 h
Toxicity to Algae EC50: 4.9 mg/l - 72 h

Biodegradability Readily biodegradable

Bioaccumulation Not expected

SECTION 13: DISPOSAL CONSIDERATION

Waste materials and empty container must be disposed of in accordance with applicable federal, state/provincial, and local regulations. Regulations may vary by location. Empty containers may hold hazardous vapors. Do not weld or expose to heat.

SECTION 14: TRANSPORT INFORMATION

DOT Description


UN1263, PAINT, 3, PGII

SECTION 15: REGULATORY INFORMATION

TSCA Status In compliance with TSCA inventory requirements for commercial purposes.

SARA 312 Regulated Chemical(s) 1-Chloro-4-(trifluoromethyl)-benzene
Acetone
Talc (non-fibrous)
Titanium dioxide
n-Butyl alcohol
Methyl amyl ketone
Ethyl benzene

SARA 313 Regulated Chemical(s) n-Butyl alcohol
Ethyl benzene

California Prop. 65  **WARNING:** Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

PA Right to know Chemical(s) Acetone
Talc (non-fibrous)
Titanium dioxide
n-Butyl alcohol
Methyl amyl ketone
Ethyl benzene

NJ Right to know Chemical(s) Acetone



MiraVar 275 Opaque CV Sanding Sealer White

Talc (non-fibrous)
Titanium dioxide
n-Butyl alcohol
Ethyl benzene

MA Right to know Chemical(s)

1-Chloro-4-(trifluoromethyl)-benzene
Acetone
Talc (non-fibrous)
Titanium dioxide
n-Butyl alcohol
Ethyl benzene

Canada

Not Applicable.

Additional Regulatory Information

Not Applicable.

SECTION 16: OTHER INFORMATION

HMIS

MiraVar 275 Opaque CV Sanding

HEALTH	2*
FLAMMABILITY	3
REACTIVITY	0
PERSONAL PROTECTION	X

HMIS® Hazardous Material Information System

HMIS ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risk, and 4 representing significant hazards or risks. HMIS was developed as a means of identifying and communicating workplace hazards associated with paints and coatings. Ratings are to be used with a fully implemented HMIS program. The workplace employer is responsible for determining the Personal Protection (PPE) code of this material.

HMIS® is the registered mark of the American Coatings Association (ACA)

DISCLAIMER

THE INFORMATION CONTAINED HEREIN HAS BEEN COMPILED FROM SOURCES CONSIDERED TO BE RELIABLE. TO THE BEST OF OUR KNOWLEDGE AND BELIEF, ALL INFORMATION IS ACCURATE AND IS PROVIDED IN GOOD FAITH. HOWEVER, NO GUARANTEE OF ACCURACY IS MADE OR IMPLIED.