



**SECTION 1: IDENTIFICATION**

<b>Product Name</b>	Lacquer Retarder Special
<b>Product Code #</b>	650921.00
<b>Manufacturer</b>	Gemini Industries, Inc.
<b>Address</b>	421 SE 27th Street El Reno, OK 73036
<b>Phone</b>	Local: (800) 262-5710 Toll Free: (800) 444-7833
<b>Emergency Contact</b>	CHEMTREC (24HR Emergency Telephone), call: 1-800-424-9300 International CHEMTREC, call: 1-800-255-3924
<b>Recommended Use/Restrictions</b>	Refer to technical data sheet or product label for more information.

**SECTION 2: HAZARD(S) IDENTIFICATION**

<b>Classifications</b>	Acute Toxicity - Oral: Category 4 Acute Toxicity - Skin: Category 4 Acute Toxicity - Inhalation: Category 4 STOT Single Exposure: Category 3 Flammable Liquid: Category 3
<b>Pictograms</b>	 
<b>Signal Word</b>	Warning
<b>Hazard Statements</b>	H302   Harmful if swallowed. H312   Harmful if in contact with skin. H332   Harmful if inhaled. H336   May cause drowsiness or dizziness. H226   Flammable liquid and vapor.
<b>Precautionary Statements</b>	P210   Keep away from heat/sparks/open flames/hot surfaces. - No smoking. P233   Keep container tightly closed. P240   Ground/bond container and receiving equipment. P241   Use explosion-proof electrical/ventilating/lighting/other equipment. P242   Use only non-sparking tools. P243   Take precautionary measures against static discharge. P261   Avoid breathing dust/fume/gas/mist/vapors/spray. P264   Wash any exposed body parts thoroughly after handling. P270   Do not eat, drink or smoke when using this product. P271   Use only outdoors or in a well-ventilated area. P280   Wear protective gloves/protective clothing/eye protection/face protection. P301 + P312   IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. P302 + P352   IF ON SKIN: Wash with plenty of soap and water. P303 + P361 + P353   IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. P304 + P340   IF INHALED: Remove victim to fresh air and keep at rest in a



position comfortable for breathing.  
P312 | Call a POISON CENTER or doctor/physician if you feel unwell.  
P322 | Specific measures (see supplemental first aid instruction on this label if immediate measures such as specific cleansing agent is advised).  
P330 | Rinse mouth.  
P363 | Wash contaminated clothing before reuse.  
P370 + P378 | In case of fire: Use appropriate media for extinction if water increases risk.  
P403 + P233 | Store in a well-ventilated place. Keep container tightly closed.  
P403 + P235 | Store in a well-ventilated place. Keep cool.  
P405 | Store locked up.  
P501 | Dispose of contents/container to appropriate waste disposal entity in accordance with local/regional/national/international regulation.

**Percent of the mixture consisting of ingredient(s) of unknown toxicity**

To the best of our knowledge, there are no additional ingredient(s) present requiring hazardous reporting or health warnings.

**SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS**

<b>Reportable Components</b>	<b>% of Comp.</b>	<b>CAS No.</b>
ISOBUTYL ISOBUTYRATE	50 - 60%	97-85-8
METHYL AMYL KETONE	40 - 50%	110-43-0

**SECTION 4: FIRST AID MEASURES**

<b>General Advice</b>	Have Safety Data Sheet available when calling Poison Control Center (1-800-222-1222) or physician; or when going to the emergency room.
<b>Eyes</b>	Immediately flush eye with plenty of water for 15 minutes, while lifting upper and lower eyelids. Remove contact lenses if present and easy to do. Continue rinsing. Check eye for chemical burns. Get medical attention.
<b>Skin</b>	Immediately wash with soap and water. Remove contaminated clothing and shoes. Wash or clean thoroughly before reuse. Get medical attention if irritation persists.
<b>Inhalation</b>	Remove to exposure to fresh air. If breathing is difficult, give oxygen. If breathing is stopped, give artificial respiration. Keep person warm and quiet. Get medical attention.
<b>Ingestion</b>	DO NOT INDUCE VOMITING! Call Poison Control Center, (1-800-222-1222) or physician immediately. NOTE: Aspiration of solvents may result in chemical pneumonia.

**SECTION 5: FIRE FIGHTING MEASURES**

<b>Fire Hazard</b>	Yes
<b>Extinguishing Media</b>	Foam, CO2, Dry Chemical, Water Mist
<b>Special Protective Equipment and</b>	Evacuate all unnecessary personnel. Use full protective equipment. Cool closed containers to prevent pressure build-up and possible explosion. Direct water



## Lacquer Retarder Special

### Firefighting Procedures

stream is not recommended for oil base fires. Product may float and reignite on surface of water. Do not allow product or runoff from fire control measures to enter storm or sanitary sewers or waterways.

### Unusual Fire & Explosion

Explosive vapor mixtures may form which is dangerous when exposed to heat and flame. Vapors are heavier than air and may travel along the ground, or be moved by ventilation, and ignited by pilot lights, stoves, heaters, electric motors, sparks, flame, smoking, static discharge or other ignition sources even at location distant from material handling site. Free falling stream of liquid may cause static electricity build-up and create fire hazard.

### Hazardous Combustion Products

See Section 10

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### Personal Precautions

Avoid any uncontrolled release of material. Wear chemical splash goggles, impervious gloves, appropriate respirators, and protective clothing until all hazards are known.

### Spills / Leaks

If spill/leak occurs, eliminate ignition sources and ventilate area. Evacuate all unnecessary personnel. Wear full protective equipment. Dike drains to prevent entering storm or sanitary sewers, rivers, streams, or waterways. Contain spill and cover with inert absorbent material. Clean using non-sparking tools (aluminum, brass, copper) and place mixture into containers for disposal. Note: Some spills/releases may require special reporting to local, state or federal agencies.

## SECTION 7: HANDLING AND STORAGE

### Handling

Handle using good industrial hygiene and safety practices. Avoid breathing vapors, spray mists, or dusts. Avoid contact with eyes and skin. Do not take internally. Use adequate ventilation, respiratory and personal protection. Avoid spraying hot surfaces.

### Storage

Keep liquid and vapor away from heat, sparks, and flame. Turn off or remove all sources of ignition. Use proper methods of ventilation to prevent vapor buildup. Avoid contact with hot metal surfaces. Avoid free fall of liquids. Ground and bond fixed equipment, pails, drums and other transfer containers. Do not reuse, weld, drill, or heat empty containers which may contain explosive vapors.

Keep container closed when not in use and during transit. Store container in an upright position in a cool, dry environment and protect from damage. Use adequate ventilation. Follow label warnings until thoroughly cleaned or until container is sent for disposal. Do not remove or deface labels until empty containers have been destroyed or thoroughly cleaned. Do not transfer product to unlabeled containers. Do not store above 120 deg. F (50 deg. C).

## SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION



## Exposure Limits

Chemical Description	OSHA PEL	ACGIH TLV	Other
Isobutyl isobutyrate Methyl amyl ketone	NOT EST. 100 ppm	NOT EST. 50 ppm	NOT EST. 233 mg/m3

## Engineering Controls

USE ONLY WITH ADEQUATE VENTILATION. Provide mechanical ventilation, local exhaust or other appropriate means of ventilation to prevent build-up of vapor or dust. Keep worker exposure to airborne contaminants below suggested or allowable limits. Keep area vapor and/or dust concentrations below lower explosive limits. Eye wash and safety showers are recommended in the workplace.

## Personal Protective Equipment

<b>Hand</b>	Wear impermeable, chemical resistant gloves to prevent skin contact. Consult safety equipment supplier for specific recommendations of construction material. Wash hands with soap and water after using and before eating or using tobacco products.
<b>Eyes</b>	Wear chemical goggles designed to protect eyes against vapor, liquid splash and mists unless full-face respirator is worn. Ensure eye wash and safety showers are near workstations. NOTE: Contact lenses may contribute to the severity of an eye injury and should be removed immediately if exposure occurs.
<b>Skin</b>	Wear protective clothing, including headcap, to avoid skin contact with liquid or overspray. Thoroughly clean contaminated clothing and shoes before reuse.
<b>Respiratory</b>	USE ADEQUATE VENTILATION! Ensure fresh air entry during application and drying. If you experience eye watering, headache, dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved for the hazardous ingredients listed in Section 3) during and after application. If appropriate, use respirator pre-filter or dust/particle mask to avoid breathing sanding dust Follow respirator manufacturer's instructions for use. Periodically monitor exposure levels to hazardous ingredients listed in Section 3 and review permissible exposure limits above.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	Clear liquid	<b>Upper Flammability/Explosive Limit</b>	7.90
<b>Odor</b>	Mild solvent	<b>Lower Flammability/Explosive Limit</b>	1.00
<b>pH value</b>	No Data	<b>Vapor Pressure</b>	2.00
<b>Freezing Point (F)</b>	No Data	<b>Vapor Density</b>	3.94
<b>Boiling Point (F)</b>	No Data	<b>Vapor Temperature</b>	68.00
<b>Boiling Range</b>	298.00 - 304.00	<b>Relative Density/Specific Gravity</b>	6.96906
<b>Flash Point (F)</b>	102.00	<b>Solubility</b>	Minimally Water Soluble
<b>Flash Point</b>	P Marten	<b>Partition Coefficient</b>	No Data



<b>Method Used</b>			
<b>Evaporation Rate</b>	Moderate compared to butyl acetate	<b>Auto-Ignition Temperature</b>	No Data
<b>Flammability</b>	Yes	<b>Decomposition Temperature</b>	No Data
<b>Viscosity</b>	See Tech Data Sheet		

### SECTION 10: STABILITY AND REACTIVITY

<b>Chemical Reactivity</b>	Will not occur.
<b>Chemical Stability</b>	Stable.
<b>Conditions to Avoid</b>	High temperatures, humidity, ignition sources and vapor build-up.
<b>Materials to Avoid</b>	Strong oxidizers
<b>Hazardous Decomposition</b>	Carbon Monoxide, Carbon Dioxide, Hydrocarbons, Aldehydes, Other Organic Compounds

### SECTION 11: TOXICOLOGICAL INFORMATION

#### Acute Toxicity

Reportable Components	LD50 Oral	LC50 Inhalation	LD50 Dermal
Isobutyl isobutyrate Methyl amyl ketone	12,800 mg/kg 1,600 mg/kg	Not available > 16 mg/l (4H)	> 17,760 mg/kg > 5,000 mg/kg

#### Inhalation

##### Description of Effects From Short- and Long-Term Exposure:

Vapors and mists irritate nose, throat, and lungs (burning, stinging, coughing). May cause headache, dizziness, nausea, weakness, shortness of breath and loss of coordination. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Exposure to extremely high vapor concentrations may cause unconsciousness and asphyxiation. Dust, sanding dusts and particles may cause nose and throat irritation. Harmful if inhaled.

#### Ingestion

##### Description of Effects From Short- and Long-Term Exposure:

Causes nausea, vomiting, diarrhea and severe central nervous system depression (headache, dizziness, nausea, loss of coordination). Harmful if swallowed.

#### Eyes

##### Description of Effects From Short- and Long-Term Exposure:

Contact with liquid or vapors causes severe irritation (redness, watering, itching, stinging, blurred vision) and possible cornea damage.

#### Skin



**Description of Effects From Short- and Long-Term Exposure:**

Contact causes mild to severe irritation (dryness, itching, cracking, rash and swelling) and possible burns with prolonged contact. Harmful if in contact with skin.

**Carcinogen Information**

Not Applicable.

**Carcinogens Listing**

<b>NTP</b>	No
<b>IARC</b>	No
<b>OSHA</b>	No

**SECTION 12: ECOLOGICAL INFORMATION**

**Aquatic Toxicity**

Methyl amyl ketone

Toxicity to Fish LC50: 126-137 mg/l - 96

Toxicity to Algae EC50: 98.2 mg/l - 72 h

**Biodegradability** Readily biodegradable

**Bioaccumulation** Not expected

**SECTION 13: DISPOSAL CONSIDERATION**

Waste materials and empty container must be disposed of in accordance with applicable federal, state/provincial, and local regulations. Regulations may vary by location. Empty containers may hold hazardous vapors. Do not weld or expose to heat.

**SECTION 14: TRANSPORT INFORMATION**

**DOT Description**

UN1263, PAINT RELATED MATERIAL, 3, PGIII

**SECTION 15: REGULATORY INFORMATION**

**TSCA Status** In compliance with TSCA inventory requirements for commercial purposes.

**SARA 312 Regulated Chemical(s)** Isobutyl isobutyrate  
Methyl amyl ketone

**SARA 313 Regulated Chemical(s)**



# Safety Data Sheet

## Lacquer Retarder Special

Date Issued

09/25/2020

**California Prop. 65** Not Applicable.  
**PA Right to know Chemical(s)** Methyl amyl ketone

**NJ Right to know Chemical(s)** Isobutyl isobutyrate

**MA Right to know Chemical(s)**

**Canada** Not Applicable.

**Additional Regulatory Information** Not Applicable.

### SECTION 16: OTHER INFORMATION

#### HMIS

Lacquer Retarder Special

HEALTH	2*
FLAMMABILITY	2
REACTIVITY	0
PERSONAL PROTECTION	X

#### HMIS® Hazardous Material Information System

HMIS ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risk, and 4 representing significant hazards or risks. HMIS was developed as a means of identifying and communicating workplace hazards associated with paints and coatings. Ratings are to be used with a fully implemented HMIS program. The workplace employer is responsible for determining the Personal Protection (PPE) code of this material.

HMIS® is the registered mark of the American Coatings Association (ACA)

#### DISCLAIMER

THE INFORMATION CONTAINED HEREIN HAS BEEN COMPILED FROM SOURCES CONSIDERED TO BE RELIABLE. TO THE BEST OF OUR KNOWLEDGE AND BELIEF, ALL INFORMATION IS ACCURATE AND IS PROVIDED IN GOOD FAITH. HOWEVER, NO GUARANTEE OF ACCURACY IS MADE OR IMPLIED.